

Product Data Sheet

MAK METAMOL

ISO VG: 32, 68, 100 & 220

DESCRIPTION

These are high quality oils with carefully selected additives. The additive combination imparts the fractional characteristics necessary to prevent stick-slip and jerky motion.

PERFORMANCE BENEFITS

- Exhibits very good oxidation stability
- Contains anti-wear, non-drip and oiliness additives

APPLICATIONS

These oils are recommended for lubrication of slides and tables of machine tools for both horizontal and vertical guide ways.

PERFORMANCE LEVEL

- Proprietary grade

Characteristics	IS 1448	Typical Figures			
		32	68	100	220
Appearance	--	Clear & Bright	Clear & Bright	Clear & Bright	Clear & Bright
Density at 15° C	P:16	0.878	0.885	0.893	0.910
K.V at 40° C, cSt	P:25	32.1	68.5	100.1	220.2
Viscosity Index	P:56	101	98	96	94
Pour Point, °C	P:10	-9	-9	-6	-6
Flash Point, (COC), °C	P:69	222	236	248	260
Foaming Characteristics/Stability	P:67	Nil	Nil	Nil	Nil
a) Sequence I					
b) Sequence II					
c) Sequence III					

Health and Safety

These oils are not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Bharat Petroleum Corporation Ltd.

Technical Services

A¹ Installation, Sewree (East), Mumbai – 400 015

Phone: 022-24176354, Fax: 022-24182511 / 24166512

email: z_techservices@bharatpetroleum.in

Edition: R&D / Indl / 047 / Issue 1 / Oct, 2008